


Zoom Camera

ATC-HZ7825Z-LT


- 1/2.8" EXMOR R Progressive Scan CMOS
- 300x AF Zoom(25x optical zoom, 12x digital zoom)
- 1080p 60(50fps)
- Mechanical Day&Night
- True WDR
- 3D DNR, Defog
- UART RS232-TTL(Pleco-D, Pelco C, VISCA, Hitachi)



Zoom Camera

ATC-HZ7825Z-LT

Dimensions



Specifications

Image Sensor	1/2.8" Exmor R Progressive Scan CMOS	
Effective Pixels	2.13MP 1945(H) x 1097(V)	
Video Output mode	HD-SDI/EX-SDI(V1.0)/CVBS TVI/LVDS	
Max. Video Resolution	HD-SDI/LVDS:1080p@60(50fps), EX-SDI/TVI:1080@30(25fps)	
Synchronization system	Internal	
Min.Illumination	Day mode: 0.1(Lux(F1.6)) Night mode: 0.06Lux(F1.6/ IR-cut filter on) Sens-Up off, AGC28dB	
S/N Rate	More than 52dB(AGC off, Sens-Up off)	
Lens	Type	AF Optical zoom lens(DC Iris), IR Corrective
	Focal Length	f=5.3~130mm
	F-value	F1.6(W)~4.3(T)
	Angle of View	Horizontal 59°(W)~2.4°(T), Vertical 33.6°(W)~1.4°(T)
Zoom ratio	Optical 25x / Digital 12x	
Focus Min.Working Distance	0.1m(Wide)/1.5m(Tele)~∞	
Focus Control	Auto/Manual/Interval/One Shot/Preset	
AE mode	Auto/Shutter Priority/Iris Priority/Manual	
Brightness	0~14	
Manual Shutter	1/1, 1/2, 1/4(3), 1/8(6), 1/15(12), 1/30(25), 1/60(50)~1/30000	
Manual Iris	F1.6~F19, Close	
Sense-up	Off~32fields	
ETC	Spot AE, Slow AE	
D&N Mode	Auto/Day(Color)/Night(BW)/External-H or L	
White Balance	AUTO/ATW/Indoor/Outdoor/One Push/Manual	
Image Freeze	Off/On	
Image Flip	Off/Horizontal/Vertical/H+V(180° Flip)	
Privacy Mask Zone	16 Zones/14 mask color selectable, semi-transparency	
Digital Image Stabilization	Yes	
Motion Detection	4 Zones	

D-WDR	Off/Low/Middle/High	
WDR	Off/Low/Middle/High	
BLC	Off/On, Area selectable	
HLC	Off/0~20, Color selectable	
AGC	Max.58dB	
Sharpness	Adjustable(0~15)	
3D-DNR	Off/On(1~5)	
2D-DNR	Auto/Manual	
Defog	Off/Low/Middle/High	
Preset Position	256 position Presets(Zoom,Focus), 16 Memory Presets, Custom Preset	
Language	English, Japanese, Russian, Spanish, German, France, Portuguese, Chinese	
UART	Remote	RS232 TTL +5.0V(+3.3V compatible)
	Protocol	VISCA/Pelco-D/Pelco-P/Hitachi: Automatic Detection
UART	Baud rate	2400/4800/9600/19200/38400/57600/115200bps
	UTC	TVI-UTC
Supply Voltage	12VDC(9V to 15VDC)	
Power Consumption	Max.5.2W / Non-working zoom&focus 3.2W	
Dimension(mm)	50.0x58.8x96.1mm	
Weight	Approx.240g	
Operating Temperature	-10°C~+50°C, Humidity(20~80%)	
Storage Temperature	-20°C~+60°C, Humidity(20~95%)	