


Zoom Camera

ATC-HZ7830Z-LA


- 1/2.8" SONY EXMOR Progressive Scan CMOS
- 360x AF Zoom(30x optical zoom, 12x digital zoom)
- 1080p 60(50fps)
- Mechanical Day&Night
- True WDR
- 3D DNR, Defog
- UART RS232-TTL(Pleco-D, Pelco C, VISCA, Hitachi)



Zoom Camera

ATC-HZ7830Z-LA

Dimensions



Specifications

Image Sensor	1/2.8" Exmor R Progressive Scan CMOS	D-WDR	Off/Low/Middle/High	
Effective Pixels	2.13MP 1945(H) x 1097(V)	WDR	Off/Low/Middle/High	
Video Output mode	Main : AVI/LVDS, Sub : HD-SDI/EX-SDI(V1.0)/CVBS	BLC	Off/On, Area selectable	
Max. Video Resolution	HD-SDI/LVDS:1080p@60(50fps), EX-SDI/AVI:1080p@30(25fps)	HLC	Off/0~20, Color selectable	
Synchronization system	Internal	AGC	Max.58dB	
Min.Illumination	Day mode: 0.1(Lux(F1.6)) Night mode: 0.06Lux(F1.6/ IR-cut filter on) Sens-Up off, AGC28dB	Sharpness	Adjustable(0~15)	
S/N Rate	More than 52dB(AGC off, Sens-Up off)	3D-DNR	On/Off(1~5)	
Lens	Type	AF Optical zoom lens(DC Iris), IR Corrective	2D-DNR	Auto/Manual
	Focal Length	f=5.0~150mm	Defog	Off/Low/Middle/High
	F-value	F1.6(W)~4.3(T)	Preset Position	256 position Presets(Zoom,Focus), 16Memory Presets, Custom Preset
	Angle of View	Horizontal 59.2°(W)~2.0°(T), Vertical 33.8°(W)~1.15°(T)	Language	English, Japanese, Russian, Spanish, German, France, Portuguese, Chinese
Zoom ratio	Optical 30x / Digital 12x	UART	Remote	RS232 TTL +5.0V(+3.3V compatible)
Focus Min.Working Distance	0.1m(Wide)/1.5m(Tele)~∞	Protocol	VISCA/Pelco-D/Pelco-P/Hitachi: Automatic detection	
Focus Control	Auto/Manual/Interval/One Shot/Preset	Baud rate	2400/4800/9600/19200/38400/57600/115200bps	
AE mode	Auto/Shutter Priority/Iris Priority/Manual	UTC	AVI-UTC	
Brightness	0~14	Supply Voltage	12VDC(9V to 15VDC)	
Manual Shutter	1/1, 1/2, 1/4(3), 1/8(6), 1/15(12), 1/30(25), 1/60(50)~1/30000	Power Consumption	Max.5.2W / Non-working zoom&focus 3.2W	
Manual Iris	F1.6~F19, Close	Dimension(mm)	50x58.8x96.1mm	
Sense-up	Off~32fields	Weight	Approx.240g	
ETC	Spot AE, Slow AE	Operating Temperature	-10°C~+50°C, Humidity(20~80%)	
D&N Mode	Auto/Day(Color)/Night(BW)/External-H or L	Storage Temperature	-20°C~+60°C, Humidity(20~95%)	
White Balance	AUTO/ATW/Indoor/Outdoor/OnePush/Manual	Support Video Output	-	
Image Freeze	Off/On			
Image Flip	Off/Horizontal/Vertical/H+V(180° Flip)			
Privacy Mask Zone	16 Zones/14 mask color selectable, semi-transparency			
Digital Image Stabilization	Yes			
Motion Detection	4 Zones			