


Zoom Camera

ATC-HZ5636W-LP


- 1/2" SONY EXMOR R Progressive Scan CMOS
- 432x AF Zoom(36x optical zoom, 12x digital zoom)
- 1080p 60/50/30/25fps
- Mechanical Day&Night
- True WDR
- 3D DNR, Defog
- UART RS232-TTL(Pleco-D, Pelco C, VISCA, Hitachi)



Zoom Camera

ATC-HZ5636W-LP

Dimensions



Specifications

Image Sensor	1/2" SONY EXMOR R Progressive Scan CMOS	
Effective Pixels	2.13MP 1945(H) x 1097(V)	
Video Output mode	LVDS / Parallel / CVBS	
Max. Video Resolution	LVDS / Parallel :1080p@60(50fps)	
Synchronization system	Internal / External Option	
Min.Illumination	Day mode: 0.1Lux(F1.5) Night mode: 0.05Lux(F1.5/ IR-cut filter on) DSS OFF, AGC45dB	
S/N Rate	More than 55dB(AGC off, DSS off)	
Lens	Type	AF Optical zoom lens(DC Iris), IR Corrective
	Focal Length	f=6.0mm~216mm
	F-value	F1.5(W)~4.8(T)
	Angle of View	Horizontal 58.4°(W)~2.2°(T), Vertical 34.1°(W)~1.2°(T)
Zoom ratio	Optical 36x / Digital 12x	
Focus Min.Working Distance	0.1m(Wide)/1.5m(Tele)-∞	
Focus Control	Auto/Interval/One Push/Manual/Presets	
AE mode	Auto/Shutter Priority/Iris Priority/AGC Priority/Manual	
Brightness	0~14	
Manual Shutter	1/1, 1/2, 1/4(3), 1/8(6), 1/15(12), 1/30(25), 1/60(50)~1/10000	
Manual Iris	F1.6~F32, Close	
Sense-up	Off~32fields	
ETC	Spot AE, Slow AE	
D&N Mode	Auto/Day(Color)/Night(BW)/External-H or L	
White Balance	AUTO/One Push/Indoor/Outdoor/ATW/Manual	
Image Freeze	Off/On	
Image Flip	Off/Horizontal/Vertical/H+V(180° Flip)	
Privacy Mask Zone	8 Zones/14 mask color selectable	
Digital Image Stabilization	Yes	
Motion Detection	4 Zones	

D-WDR	Off/Low/Middle/High	
WDR	Off/On, Adjustable(Level:0~29, Contrast:0~5, Bright: 0~19)	
BLC	Off/On, Area selectable	
HLC	Off/On, Area selectable	
AGC	Max.72dB	
Sharpness	Adjustable(0~15)	
3D-DNR	Off/Auto/Low/Middle/High	
2D-DNR	Off/Auto/Low/Middle/High	
Defog	Off/On/Auto	
Presets Position	256 position Presets(Zoom,Focus), 16Memory Presets, Custom Preset	
Language	English	
UART	Remote	RS232 TTL +5.0V(+3.3V compatible)
	Protocol	VISCA/Pelco-D/Pelco-P/Hitachi: Automatic detection
	Baud rate	2400/4800/9600/19200/38400/57600/115200bps
UTC	-	
Supply Voltage	12VDC(9V to 15VDC)	
Power Consumption	Max.6.8W / Non-working zoom&focus 4.2W	
Dimension(mm)	55.0x64.0x123mm	
Weight	Approx.380g	
Operating Temperature	-10°C~+50°C, Humidity(20~80%)	
Storage Temperature	-20°C~+60°C, Humidity(20~95%)	